



PLF2-0512E-xxxxx-M

Closed circuit cooling towers

Engineering data

REMARK: Do not use for construction. Refer to factory certified dimensions & weights. This page includes data current at time of publication, which should be reconfirmed at the time of purchase. In the interest of product improvement, specifications, weights and dimensions are subject to change without notice.

General notes

1. Standard refrigerant in- and outlet connection sizes are ND100. Consult your local BAC representative for locations. Refrigerant connections are closed and coils are filled with an inert gas.
2. Unit height is indicative. For precise value refer to certified print.
3. Shipping/operating weights indicated are for units without accessories such as sound attenuators, discharge hoods, etc. Consult factory certified prints to obtain weight additions and the heaviest section to be lifted. Operating weights shown in the tables is based on total unit weight, weight of refrigerant operating charge and basin filled to overflow level.
4. Drawings show the standard right hand arrangement (air inlet side on the right when facing the connection end). Left hand arrangement can be supplied upon request.

[PLF2 cooling tower performance at standard conditions - 30% EG](#)

[PLF2 cooling tower performance at standard conditions - 30% PG](#)

[PLF2 cooling tower performance at standard conditions - water](#)

[PLF2 cooling tower - pressure drop](#)

Last update: 31/01/2022

PLF2-0512E-xxxxx-M





1. Fluid in ND100; 2. Fluid out ND100; 3. Make up ND40; 4. Overflow ND80; 5. Drain ND50; 6. Bleed ND25; 7. Treated water in ND20; 8. Access door.

Model	Weights (kg)			Dimensions (mm)			Air Flow (m³/s)	Fan Motor (kW)	Water Flow (l/s)	Pump Motor (kW)	Coil Volume (L)
	Oper. Weight (kg)	Ship. Weight(kg)	Heaviest Section (kg)	L	W	H					
PLF2 0512E- 2D2AS- M	3584	2173	1143	3651	1435	3070	21.6	(4x) 4.05	9.6	(1x) 1.5	(1x) 292
PLF2 0512E- 3D2AS- M	3972	2425	1282	3651	1435	3305	20.7	(4x) 4.05	9.6	(1x) 1.5	(1x) 427
PLF2 0512E- 4D2AS- M	4350	2667	1524	3651	1435	3540	20.0	(4x) 4.05	9.6	(1x) 1.5	(1x) 563
PLF2 0512E- 5D2AS- M	4729	2911	1768	3651	1435	3775	19.3	(4x) 4.05	9.6	(1x) 1.5	(1x) 699
PLF2 0512E- 6D2AS- M	5051	3098	1954	3651	1435	3789	18.8	(4x) 4.05	9.6	(1x) 1.5	(1x) 835
PLF2 0512E- 7D2AS- M	5420	3330	2187	3651	1435	3980	18.3	(4x) 4.05	9.6	(1x) 1.5	(1x) 970