



SP 3A D610-B - T610-B

Previous generation products

Engineering data

REMARK: Do not use for construction. Refer to factory certified dimensions & weights. This page includes data current at the time of publication, which should be reconfirmed at the time of purchase. In the interest of product improvement, specifications, weights and dimensions are subject to change without notice.

Last update: 24/04/2024

SP 3A D610-B - T610-B



1. Fluid inlet connections; 2. Fluid outlet connections; 3. Pre-cooler water drain; 4. Electrical panel; 5. Pre-cooler city water connection; 6. Pre-cooler piping drain.
On models SP3A D610-B the fluid-in connections are located at the opposite side of the unit.

Model	Nr. of Fans	Weights (kg)			Dimensions (mm)			Air Flow (m³/s)		Tube Internal Volume (dm³)	Surface (m²)	Connections
		Oper. Weight (kg)	Ship. Weight(kg)	Heaviest Section (kg)	L	W	H	Δ	Y			
SP 3 A-D610-B	3	2130	1790	1790	4016	2206	2575	22.2	17.3	140.0	2388.0	2
SP 3 A-H610-B	3	2130	1790	1790	4016	2206	2575	22.2	17.3	140.0	2388.0	2
SP 3 A-L610-B	3	2130	1790	1790	4016	2206	2575	22.2	17.3	140.0	2388.0	2
SP 3 A-M610-B	3	2130	1790	1790	4016	2206	2575	22.2	17.3	140.0	2388.0	2
SP 3 A-S610-B	3	2130	1790	1790	4016	2206	2575	22.2	17.3	140.0	2388.0	2
SP 3 A-T610-B	3	2130	1790	1790	4016	2206	2575	22.2	17.3	140.0	2388.0	2