



Table with columns for Condition Reference #, Wet Bulb °C, Range °C, Approach °C, Inlet Water Temperature °C, Outlet Water Temperature °C, Model Capacity (t/s), and 48 columns of performance data (1-48). Rows include various model codes like PFI 0709E-203DS-H, PFI 0709E-301DS-H, etc.



PFI Closed Circuit Cooling Tower Performance at Standard Conditions

Table with columns for Condition Reference #, Wet Bulb °C, Range °C, Approach °C, Inlet Water Temperature °C, Outlet Water Temperature °C, Model Capacity (t/s), and 48 numbered columns for performance metrics. Rows include various PFI models like PFI 0709E-6018T-L, PFI 0709E-6015D-H, etc.



PFI Closed Circuit Cooling Tower Performance at Standard Conditions

Table with columns for Condition Reference #, Wet Bulb °C, Range °C, Approach °C, Inlet Water Temperature °C, Outlet Water Temperature °C, Model Capacity (t/s), and 48 columns of performance data (flow rates, temperatures, etc.) for various PFI cooling tower models.



Table with columns for Condition Reference #, Wet Bulb °C, Range °C, Approach °C, Inlet Water Temperature °C, Outlet Water Temperature °C, Model Capacity (W), and 48 columns of performance data (W/s).



Table with columns for Condition Reference #, Wet Bulb °C, Range °C, Approach °C, Inlet Water Temperature °C, Outlet Water Temperature °C, and Model Capacity (Us) for various PFI cooling tower models (e.g., PFI 0812E-2042Z-J, PFI 0812E-3042Z-M) across 48 different reference points.



Table with columns for Condition Reference #, Wet Bulb °C, Range °C, Approach °C, Inlet Water Temperature °C, Outlet Water Temperature °C, Model Capacity (Wt), and a grid of 48 columns representing different models (PFI 0812E-6018T-M to PFI 0818E-4042Z-M).



PFI Closed Circuit Cooling Tower Performance at Standard Conditions

Table with columns for Condition Reference #, Wet Bulb °C, Range °C, Approach °C, Inlet Water Temperature °C, Outlet Water Temperature °C, Model Capacity (W), and a grid of performance data for various PFI models (e.g., PFI 0818E-4045E-M, PFI 1009E-2048S-K) across different operating conditions.



PFI Closed Circuit Cooling Tower Performance at Standard Conditions

Table with columns for Condition Reference #, Wet Bulb °C, Range °C, Approach °C, Inlet Water Temperature °C, Outlet Water Temperature °C, Model Capacity (t/s), and 48 numbered columns for performance metrics. Rows include various PFI 1009E models (e.g., 4D18T-L, 4D18T-M, 4D18T-N, etc.) and their corresponding performance values.





PFI Closed Circuit Cooling Tower Performance at Standard Conditions

Table with columns for Condition Reference #, Wet Bulb °C, Range °C, Approach °C, Inlet Water Temperature °C, Outlet Water Temperature °C, Model Capacity (t/s), and 48 numbered columns for performance metrics. Rows include various PFI models like PFI 1012E-3010Z-N, PFI 1012E-3010Z-M, etc.



Table with columns for Condition Reference #, Wet Bulb °C, Range °C, Approach °C, Inlet Water Temperature °C, Outlet Water Temperature °C, Model Capacity (t/s), and 48 numbered columns for performance metrics.



Table with columns for Condition Reference #, Wet Bulb °C, Range °C, Approach °C, Inlet Water Temperature °C, Outlet Water Temperature °C, and Model Capacity (W) for various PFI cooling tower models (e.g., PFI 1212E-302EZ-M, PFI 1212E-302EZ-L, etc.) across 48 different conditions.



Table with columns for Condition Reference #, Wet Bulb °C, Range °C, Approach °C, Inlet Water Temperature °C, Outlet Water Temperature °C, Model Capacity (t/s), and 48 numbered columns for performance metrics.



PFI Closed Circuit Cooling Tower Performance at Standard Conditions

Table with columns for Condition Reference #, Wet Bulb °C, Range °C, Approach °C, Inlet Water Temperature °C, Outlet Water Temperature °C, Model Capacity (t/s), and 48 numbered columns for performance metrics. Rows include various PFI models like 1218E-302ES-O, 1218E-302EZ-M, etc.



Table with columns for Condition Reference #, Wet Bulb °C, Range °C, Approach °C, Inlet Water Temperature °C, Outlet Water Temperature °C, and Model Capacity (W/s) for various PFI cooling tower models (e.g., PFI 1218E-404E2-O, PFI 1218E-S018S-H, etc.).